# Anti-Glare COB Downlight KV-DL-101

## SPECIFICATION



| | |
|---|---|
| **Series** | KV-DL-101 |
| **Power** | 10 W / 15 W / 20 W / 25 W / 30 W |
| **Luminous flux** | 1450 / 2150 / 2850 / 3600 / 4300 lm |
| **Cut out** | Ø105 / Ø125 / Ø145 / Ø175 / Ø200 mm |
| **Beam angle** | 38° / 60° |
| **Colour rendering** | Ra >= 90 |
| **Colour temperature** | 2700K - 5000K |
| **Control** | Non-dimming standard; Triac, 0-10V, DALI and Bluetooth (BLE) dimming available |
| **Driver** | Driver brand named on your proforma invoice |
| **Finish** | White or black |
| **On-site settings** | Power and colour temperature switch (3 settings) available; steps confirmed on your quotation |
| **Warranty** | 5 years |

## ORDERING GUIDE

| KV code | Wattage | Lumens | Beam angles | Size / cut-out | Finish |
|---|---|---|---|---|---|
| KV-DL-101-10 | 10 W | 1450 lm | 38° / 60° | Ø115 × 56 mm · cut-out Ø105 mm | White or black |
| KV-DL-101-15 | 15 W | 2150 lm | 38° / 60° | Ø136 × 70 mm · cut-out Ø125 mm | White or black |
| KV-DL-101-20 | 20 W | 2850 lm | 38° / 60° | Ø162 × 80 mm · cut-out Ø145 mm | White or black |
| KV-DL-101-25 | 25 W | 3600 lm | 38° / 60° | Ø195 × 95 mm · cut-out Ø175 mm | White or black |
| KV-DL-101-30 | 30 W | 4300 lm | 38° / 60° | Ø220 × 100 mm · cut-out Ø200 mm | White or black |