Dimmable Recessed Spotlight KV-SP-104

SPECIFICATION



Series	KV-SP-104
Power	5 W / 10 W / 15 W / 25 W / 35 W
Luminous flux	450 / 1050 / 1450 / 2350 / 3300 lm
Cut out	Ø55 / Ø75 / Ø95 / Ø125 / Ø135 mm
Beam angle	38° / 60°
Adjustment	30° tilt
Colour rendering	Ra >= 90
Colour temperature	2700K - 5000K
Control	Triac dimming standard; 0-10V and DALI available
Driver	Driver brand named on your proforma invoice
Input	220-240 V AC
Finish	White or black
On-site settings	Power and colour temperature switch (3 settings) available; steps confirmed on your quotation
Warranty	5 years

ORDERING GUIDE

KV code	Wattage	Lumens	Beam angles	Size / cut-out	Finish
KV-SP-104-5	5 W	450 lm	38° / 60°	Ø65 × 65 mm · cut-out Ø55 mm	White or black
KV-SP-104-10	10 W	1050 lm	38° / 60°	Ø87 × 78 mm · cut-out Ø75 mm	White or black
KV-SP-104-15	15 W	1450 lm	38° / 60°	Ø108 × 93 mm · cut-out Ø95 mm	White or black
KV-SP-104-25	25 W	2350 lm	38° / 60°	Ø139 × 123 mm · cut-out Ø125 mm	White or black
KV-SP-104-35	35 W	3300 lm	38° / 60°	Ø150 × 143 mm · cut-out Ø135 mm	White or black