LED Track Lighting Systems for Retail & Commercial

KV-TS-101 · KV-TS-104



SPECIFICATION

Series	KV-TS-101 (slim body) · KV-TS-102 · KV-TS-103 (short body) · KV-TS-104 Bluetooth (BLE) series
Power	15 W / 25 W / 32 W (KV-TS-101, KV-TS-102, KV-TS-103) · 25 / 30 / 35 W (KV-TS-104)
Luminous flux	2050 / 3550 / 4500 lm (15 / 25 / 32 W)
Efficacy	140 lm/W (KV-TS-101 / KV-TS-102 / KV-TS-103) · 130 lm/W (KV-TS-104)
Colour rendering	Ra >= 90 (KV-TS-101/102/103); Ra >= 80 standard, Ra >= 90 available (KV-TS-104)
Colour temperature	3000K / 4000K / 5000K (KV-TS-101/102/103) · 2800-3200K / 3700-4500K / 5300-6500K (KV-TS-104)
Beam angle	15° / 24° / 36° (zoomable 15-60° on the KV-TZ-101 spot)
Ugr	< 22
Control	Non-dimming standard; Triac, 0-10V, DALI and Bluetooth (BLE) dimming available
Driver	Integrated flicker-free driver; driver brand named on your proforma invoice
Track type	3-circuit (4-wire) track adaptor
IP rating	IP20
Finish	Black or white
Lifespan	L70 > 50,000 h (typical)
On-site settings	Power and colour temperature switch (3 settings) available; steps confirmed on your quotation
Warranty	5 years

ORDERING GUIDE

KV code	Wattage	Lumens	Beam angles	Size / cut-out	Finish
KV-TS-101-15	15 W	2050 lm	15° / 24° / 36°	Ø60 × 130 mm	Black or white
KV-TS-101-25	25 W	3550 lm	15° / 24° / 36°	Ø75 × 161 mm	Black or white
KV-TS-101-32	32 W	4500 lm	15° / 24° / 36°	Ø85 × 160 mm	Black or white
KV-TS-102-20	20 W	2850 lm	15° / 24° / 36°	Ø72 × 123 mm	Black or white
KV-TS-102-25	25 W	3550 lm	15° / 24° / 36°	Ø80 × 131 mm	Black or white
KV-TS-102-32	32 W	4500 lm	15° / 24° / 36°	Ø90 × 141 mm	Black or white
KV-TS-103-15	15 W	2050 lm	15° / 24° / 36°	Ø71 × 85 mm	Black or white
KV-TS-103-25	25 W	3550 lm	15° / 24° / 36°	Ø82 × 100 mm	Black or white
KV-TS-103-32	32 W	4500 lm	15° / 24° / 36°	Ø100 × 105 mm	Black or white