Pull-Out Gimbal Downlight KV-GD-101

SPECIFICATION



Series	KV-GD-101
Power	10 W / 15 W / 20 W / 25 W / 35 W
Luminous flux	1450 / 2150 / 2850 / 3600 / 4800 lm
Cut out	Ø95 / Ø110 / Ø125 / Ø145 / Ø175 mm
Beam angle	24° / 38° / 60°
Colour rendering	Ra >= 90
Colour temperature	2700K - 5000K
Control	Non-dimming standard; Triac, 0-10V, DALI and Bluetooth (BLE) dimming available
Driver	Driver brand named on your proforma invoice
Finish	White or black
Trim	Round trim standard; square trim available, dimensions on request
IP rating	IP20
On-site settings	Power and colour temperature switch (3 settings) available; steps confirmed on your quotation
Warranty	5 years

ORDERING GUIDE

KV code	Wattage	Lumens	Beam angles	Size / cut-out	Finish
KV-GD-101-10	10 W	1450 lm	24° / 38° / 60°	102 × 80 mm · cut-out Ø95 mm	White or black
KV-GD-101-15	15 W	2150 lm	24° / 38° / 60°	125 × 108 mm · cut-out Ø110 mm	White or black
KV-GD-101-20	20 W	2850 lm	24° / 38° / 60°	140 × 115 mm · cut-out Ø125 mm	White or black
KV-GD-101-25	25 W	3600 lm	24° / 38° / 60°	160 × 135 mm · cut-out Ø145 mm	White or black
KV-GD-101-35	35 W	4800 lm	24° / 38° / 60°	190 × 145 mm · cut-out Ø175 mm	White or black