# Recessed Tiltable Downlight KV-SP-105



## SPECIFICATION

| | |
|---|---|
| **Series** | KV-SP-105 |
| **Power** | 10 W / 15 W / 25 W / 32 W |
| **Luminous flux** | 1400 / 2100 / 3600 / 4400 lm |
| **Efficacy** | up to 140 lm/W |
| **Cut out** | Ø55 / Ø75 / Ø95 / Ø115 mm |
| **Beam angle** | 15° / 24° / 38° / 60° |
| **Adjustment** | 90° tilt |
| **Colour rendering** | Ra >= 90 |
| **Colour temperature** | 2700K - 5000K |
| **Control** | Non-dimming standard; Triac, 0-10V, DALI and Bluetooth (BLE) dimming available |
| **Driver** | Driver brand named on your proforma invoice |
| **Input** | 220-240 V AC |
| **Finish** | White or black |
| **On-site settings** | Power and colour temperature switch (3 settings) available; steps confirmed on your quotation |
| **Warranty** | 5 years |

## ORDERING GUIDE

| KV code | Wattage | Lumens | Beam angles | Size / cut-out | Finish |
|---|---|---|---|---|---|
| KV-SP-105-10 | 10 W | 1400 lm | 15° / 24° / 38° / 60° | Ø50 × 70 mm · cut-out Ø55 mm | White or black |
| KV-SP-105-15 | 15 W | 2100 lm | 15° / 24° / 38° / 60° | Ø71 × 85 mm · cut-out Ø75 mm | White or black |
| KV-SP-105-25 | 25 W | 3600 lm | 15° / 24° / 38° / 60° | Ø82 × 100 mm · cut-out Ø95 mm | White or black |
| KV-SP-105-32 | 32 W | 4400 lm | 15° / 24° / 38° / 60° | Ø100 × 105 mm · cut-out Ø115 mm | White or black |