Round Grid Downlight KV-GR-101

SPECIFICATION



Series	KV-GR-101
Power	10 W / 15 W / 25 W
Luminous flux	1400 / 2100 / 3600 lm
Efficacy	140 lm/W
Cut out	Ø75 / Ø95 / Ø115 mm
Beam angle	15° / 24° / 38° / 60°
Adjustment	Pull-down head, 350° rotation, 90° tilt
Colour rendering	Ra >= 90
Colour temperature	2700K - 5000K
Control	Non-dimming standard; Triac, 0-10V, DALI and Bluetooth (BLE) dimming available
Driver	Driver brand named on your proforma invoice
Input	220-240 V AC
Finish	White or black
On-site settings	Power and colour temperature switch (3 settings) available; steps confirmed on your quotation
Warranty	5 years

ORDERING GUIDE

KV code	Wattage	Lumens	Beam angles	Size / cut-out	Finish
KV-GR-101-10	10 W	1400 lm	15° / 24° / 38° / 60°	Ø90 × 95 mm · cut-out Ø75 mm	White or black
KV-GR-101-15	15 W	2100 lm	15° / 24° / 38° / 60°	Ø110 × 120 mm · cut-out Ø95 mm	White or black
KV-GR-101-25	25 W	3600 lm	15° / 24° / 38° / 60°	Ø130 × 140 mm · cut-out Ø115 mm	White or black