Square Grid Downlight KV-GR-102, Single and Double Head

SPECIFICATION



Series	KV-GR-102
Power	10 / 15 / 25 W single head · 2×10 / 2×15 / 2×25 W double head
Luminous flux	1400 - 3600 lm single · 2800 - 7200 lm double
Cut out	75×75 to 115×115 mm single · 75×155 to 115×230 mm double
Beam angle	15° / 24° / 38° / 60°
Adjustment	Pull-down heads, 350° rotation, 90° tilt
Efficacy	140 lm/W
Colour rendering	Ra >= 90
Colour temperature	2700K - 5000K
Control	Non-dimming standard; Triac, 0-10V, DALI and Bluetooth (BLE) dimming available
Driver	Driver brand named on your proforma invoice
Input	220-240 V AC
Finish	White or black
On-site settings	Power and colour temperature switch (3 settings) available; steps confirmed on your quotation
Warranty	5 years

ORDERING GUIDE

KV code	Wattage	Lumens	Beam angles	Size / cut-out	Finish
KV-GR-102-10	10 W	1400 lm	15° / 24° / 38° / 60°	90 × 90 × 95 mm · cut-out 75 × 75 mm	White or black
KV-GR-102-15	15 W	2100 lm	15° / 24° / 38° / 60°	110 × 110 × 120 mm · cut-out 95 × 95 mm	White or black
KV-GR-102-25	25 W	3600 lm	15° / 24° / 38° / 60°	130 × 130 × 140 mm · cut-out 115 × 115 mm	White or black
KV-GR-102-2x10	2 × 10 W	2800 lm	15° / 24° / 38° / 60°	90 × 170 × 95 mm · cut-out 75 × 155 mm	White or black
KV-GR-102-2x15	2 × 15 W	4200 lm	15° / 24° / 38° / 60°	110 × 210 × 120 mm · cut-out 95 × 190 mm	White or black
KV-GR-102-2x25	2 × 25 W	7200 lm	15° / 24° / 38° / 60°	130 × 250 × 140 mm · cut-out 115 × 230 mm	White or black