Surface-Mounted Tiltable Spotlight KV-SM-101

SPECIFICATION



Series	KV-SM-101
Power	10 W / 15 W / 25 W / 32 W
Luminous flux	1400 / 2100 / 3600 / 4400 lm
Efficacy	up to 140 lm/W
Beam angle	15° / 24° / 38° / 60°
Adjustment	90° tilt, 355° rotation
Power factor	> 0.9
Colour rendering	Ra >= 90
Colour temperature	2700K - 5000K
Control	Non-dimming standard; Triac, 0-10V, DALI and Bluetooth (BLE) dimming available
Driver	Driver brand named on your proforma invoice
Input	220-240 V AC
Finish	White or black
On-site settings	Power and colour temperature switch (3 settings) available; steps confirmed on your quotation
Warranty	5 years

ORDERING GUIDE

KV code	Wattage	Lumens	Beam angles	Size / cut-out	Finish
KV-SM-101-10	10 W	1400 lm	15° / 24° / 38° / 60°	Ø50 × 70 mm	White or black
KV-SM-101-15	15 W	2100 lm	15° / 24° / 38° / 60°	Ø71 × 85 mm	White or black
KV-SM-101-25	25 W	3600 lm	15° / 24° / 38° / 60°	Ø82 × 100 mm	White or black
KV-SM-101-32	32 W	4400 lm	15° / 24° / 38° / 60°	Ø100 × 105 mm	White or black