Zoomable Track Spotlight, Adjustable 15-60° Beam

KV-TZ-101

SPECIFICATION



Format	Cylindrical COB spot with zoom lens, 3-circuit (4-wire) adaptor
Models	KV-TZ-101-15 · KV-TZ-101-20 · KV-TZ-101-25
Power	15 W / 20 W / 25 W
Luminous flux	1450 / 2000 / 2400 lm
Bodies	Ø65×98 · Ø75×120 · Ø85×120 mm
Beam angle	15°-60° zoomable
Colour rendering	Ra >= 90
Colour temperature	3000K / 4000K / 5000K
Ugr	< 22
Control	Non-dimming standard; Triac, 0-10V, DALI and Bluetooth (BLE) dimming available
Driver	Integrated flicker-free driver, PF > 0.9; driver brand named on your proforma invoice
Track type	3-circuit (4-wire) track adaptor
Finish	Black or white
IP rating	IP20
Lifespan	L70 > 50,000 h (typical)
On-site settings	Power and colour temperature switch (3 settings) available; steps confirmed on your quotation
Warranty	5 years

ORDERING GUIDE

KV code	Wattage	Lumens	Beam angles	Size / cut-out	Finish
KV-TZ-101-15	15 W	1450 lm	15°-60° zoom	Ø65 × 98 mm	Black or white
KV-TZ-101-20	20 W	2000 lm	15°-60° zoom	Ø75 × 120 mm	Black or white
KV-TZ-101-25	25 W	2400 lm	15°-60° zoom	Ø85 × 120 mm	Black or white